
Technical Data Sheet

Material Reference	:	ARL/35 AR Highly Abrasion Resistant Soft Natural Rubber.
Description & Application	:	FOR SPECIFIC APPLICATIONS PLEASE CONTACT APPLIED RUBBER LININGS LIMITED. ARL/35 AR is a high quality soft natural rubber plant lining material with very high abrasion resistance and flexibility, plus good chemical resistance.
Temperature Range	:	- 35o to 90oC (Depending upon conditions and applications).
Specific Gravity	:	1.02
Hardness	:	37o_+ 5o SHORE 'A'
Tensile Strength	:	19.60 MPa.
Elongation At Break	:	650 %
Compression Set	:	19.5 %
Electrical Resistivity	:	N/A
Health & Safety	:	See COSSH assessments
Typical Applications	:	Slurry tanks and pipework, cyclones, sand washing plant, agitators and mixers, chutes and hoppers etc.

NOTE:- INFORMATION GIVEN IN GOOD FAITH BUT DETAILS MAY CHANGE WITHOUT PRIOR NOTIFICATION. CUSTOMERS SHOULD MAKE THEIR OWN ASSESSMENTS TO DETERMINE THAT THE MATERIALS ARE SUITABLE FOR SPECIFIC APPLICATIONS