Applied Rubber Linings Ltd

Process Plant Liners



Technical Data Sheet

Material Reference : ARL/55 AR Abrasion Resistant Natural Rubber

Description & Application : FOR SPECIFIC APPLICATIONS

PLEASE CONTACT APPLIED RUBBER LININGS LIMITED.

RUBBER LININGS LIMITED. ARL/55 AR is a hard wearing abrasion resistant natural rubber with good resistance to many

chemicals

Temperature Range : - 200 to 70oC (depending on application)

Specific Gravity : 1.13

Hardness : 530<u>+</u> 50 SHORE 'A'

Tensile Strength : 19.1 MPa

Elongation At Break : 573 %

Compression Set : 16.5 %

Electrical Resistivity : N/A

Health & Safety : See COSSH assessments

Typical Applications : Lining mining and quarry equipment,

slurry tanks & pipework, dredger pipework etc.

Tel: 01452 381849

NOTE:- INFORMATION GIVEN IN GOOD FAITH BUT DETAILS MAY

CHANGE WITHOUT PRIOR NOTIFICATION. CUSTOMERS

SHOULD MAKE THEIR OWN ASSESSMENTS TO DETERMIN E THAT THE MATERIALS ARE SUITABLE FOR SPECIFIC APPLICATIONS