Applied Rubber Linings Ltd

Process Plant Liners



Technical Data Sheet

Material Reference : ARL/60 HQN

Description & Application: FOR SPECIFIC APPLICATIONS

PLEASE CONTACT APPLIED RUBBER LININGS LIMITED.

ARL/60 HQN is a high quality neoprene plant lining compound offering good chemical resistance at temperatures

up to 100oc, plus some limited

resistance to oil.

Temperature Range : - 200 to 100oc (Depending upon application

and chemical conditions).

Specific Gravity : 1.89

Hardness : 600 + 50 SHORE 'A'

Tensile Strength : 9.3 MPa.

Elongation At Break : 650%

Compression Set : 31%

Electrical Resistivity : N/A

Health and Safety : See COSHH assessments

Typical Applications : Chemical storage tanks & pipe work, valve bodies,

riser pipes for the offshore oil industry.

Tel: 01452 381849

NOTE:- INFORMATION GIVEN IN GOOD FAITH BUT DETAILS MAY

CHANGE WITHOUT PRIOR NOTIFICATION. CUSTOMERS

SHOULD MAKE THEIR OWN ASSESSMENTS TO DETERMINE THAT THE MATERIALS ARE SUITABLE FOR SPECIFIC APPLICATIONS.